2025 CAN-AM MAVERICK X3 X RC TURBO RR



Hybrid White & Legion Red

ENGINE TURBO RR

Туре	200 hp, Rotax [®] ACE (Advanced Combustion Efficiency) 900 cc turbocharged triple-cylinder engine, liquid-cooled with integrated intercooler and high-performance air filter
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	pDrive primary and Quick Response System X (QRS-X) CVT with high airflow, L/H/N/R/P
Drive Train	Lockable front differential with exclusive Smart-Lok* technology True 4-modes traction system: 2WD/4WD with front diff. lock/ 4WD ROCK/4WD TRAIL
Power Steering	High-torque Tri-Mode Dynamic Power Steering (DPS™)
SUSPENSIONS	
Front Suspension	Trophy Truck-inspired double arched A-arm with sway bar 22 in. (55.9 cm) suspension travel
Front Shocks	FOX [†] 2.5 PODIUM RC2 [†] Piggyback with bypass, dual-speed compression and rebound adjustments
Rear Suspension	4-link Torsional Trailing Arm X (TTX) with sway bar and arched lower links 24 in. (61 cm) suspension travel
Rear Shocks	FOX [†] 3.0 PODIUM RC2 [†] with bypass, dual-speed compression and rebound adjustments
TYRES & WHEELS	
Front Tyres	XPS Trac Force 32 x 10 x 15 in.
Rear Tyres	XPS Trac Force 32 x 10 x 15 in.
Wheels	15 in. cast-aluminium beadlock
BRAKES	
Front	Dual 262 mm disc brakes with hydraulic twin-piston callipers
Rear	Dual 248 mm disc brakes

PACKAGE HIGHLIGHTS

- 200 hp. turbo charged Rotax[®] powerplant with intercooler
- 72.8 in. wide with over 55cm of suspension travel
- Smart-Lok* front differential
- + FOX † 2.5/3.0 PODIUM RC2 † shocks with bypass
- Belt monitoring system
- 850 W magneto
 7.6 in. digital display with keypad
- X-package graphics/seats
- 4-point harnesses with shoulder pads
- Can-Am LED signature lights
- 15 in. aluminium beadlock wheels
- 32 in. XPS Trac Force tyres
- Front bumper, half-doors, sport roof, intrusion bar
- Front tow hook
- 4,500-lb (2,041 kg) winch with synthetic rope
- HMWPE differential and under bumper skid plates
- · HMWPE front and rear suspension arm skid plates
- UHMWPE rock sliders

Estimated Dry Weight	1,843 lb (836 kg)
Chassis / Cage	Dual-phase 980 steel
LxWxH	134.5 x 72.8 x 68.5 in. (341.6 x 184.9 x 174 cm)
Wheelbase	102 in. (259.1 cm)
Ground Clearance	16 in. (40.6 cm)
Rack Capacity	200 lb (91 kg) with LinQ™ quick-attach
Storage Capacity	Total: 2.5 gal (9.4 L)
Fuel Capacity	10.5 gal (40 L)
Person Capacity	2
FEATURES	
Gauge	7.6 in. wide digital display with keypad
Instrumentation	DC outlet (10-A)
Anti-Theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start / Stop button
Lighting	LED headlights LED signature lights LED tail lights
Winch	4,500 lb (2,041 kg) winch with synthetic rope
Magneto	850 W
Protection	Front bumper Half-doors Aluminium roof Intrusion bar 4-point harnesses with shoulder pads UHMWPE skid plates: Full heavy-duty with differential/under bumper/front and rear suspension arm Rear tow hook Trailing Arm protector Lower A-arm protector
WARRANTY	
Factory Warranty	3-year unlimited km powertrain & Rotax® engine warranty an 1-year warranty & unlimited km on the rest of the unit



© 2024 Bombardier Recreational Products Inc. (BRP). All rights reserved. ®, TM and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. † Visco-Lok is a trademark of GKN Viscodrive GmbH. All other trademarks are the property of their respective owners. For other jurisdictions, see your local dealer. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring obligation. Some models depicted may include optional equipment. Read the side-by-side vehicle (SXS) operator's guide and watch the safety DVD before driving. For your safety, wear a helmet, eve protection and other protective gear. Fasten lateral net and seat belt at all times. Always remember that riding, alcohol and drugs don't mix. SxSs are for off-road use only. Never ride on paved surfaces or public roads. Operator must be at least 16 years old. Passenger must be at least 12 years old and able to hold hand grips and plant feet while seated against the backrest. Never engage in stunt driving and avoid excessive speed. Ride responsibly. "Smart-Lok was developed in conjunction with TEAM Industries, a market leader in the drive train industry.

